

OILSEAL TRIMMING & SLICING MACHINES



OILSEAL TRIMMING MACHINE

Specially used to trim flashes of various kinds of cup seals, Oil seals, Packing seals and soft objects.

SLICING MACHINE

Specially used in rubber industries to Slicing rings and rubber sleeves as per requirement,

OILSEAL TRIMMING MACHINE

SPECIFICATIONS

No. of Cutting Slides	2 (or) 3 on request
Stroke Length	80mm
Tilting Angle	00 to 900
Vertical Adjustment	200mm
Cross Slide Adjustment	200mm
Feed Stroke	25mm (infinitely variable)
No. of Spindle Speed	3
Spindle RPM through 'V' Belt	900, 1100, 1320
Motor Power	0.75kw, 1440 rpm
Component Holding	Vacuum, Magnetic (or) Collect Chuck
Optional	Spindle inverter & Magnetic Chuck

SLICING MACHINE

SPECIFICATIONS

Swing dia over bed	100mm
Distance between center	400mm
Carriage Travel	300mm by ball screw and Servo motor drive
Servo Motor Power	0.4kw,3000rpm, AC Servo Motor
Cross Slide Travel	70mm by Pneumatic Cylinder
Feed Stroke	25mm (infinitely variable)
Head Stock Spindle Nose	DIN 800
Size of Center	MT2
Motor Power	0.75kw, 1440 rpm
Speed Range	250 to 3000 rpm by variable speed drive
Tail stock center	MT2 revolving center
Quill Movement	100mm by Pneumatic Cylinder
Optional	Spindle Inverter



Since 1987

MARKETING DIVISION :
KASTHURI MARKETING & MANUFACTURING CONSULTANCY (P) LTD.
Manufacturing made easy

Cell: +91 - 97890 90900, +91 - 93633 90900

E-mail : info@kasthurimmc.com Website : www.kasthurimmc.com

MANUFACTURING DIVISION :

KASTHURI MACHINE BUILDERS

4H, Gandhi Nagar, G.N. Mills Post, Coimbatore - 641 029 Tel : +91-422-2643338, 2648026 Fax : +91-422-2644623

email : kmbcbe@vsnl.net Website : www.kasthurimachines.com